

Ocean Images & Co., Inc.
641 SW 4th Street, Unit 1
Cape Coral, FL 33991

Phone: (800) 409-2469
(239) 458-7155
Fax: (239) 458-1558
Email: keith@oceanimagesinc.com
Web: www.oceanimagesinc.com



Your Ocean Images housing is designed to provide years of trouble-free service with a minimum of care. It is constructed of durable, corrosion resistant materials that are well suited for the marine environment. These instructions outline the procedures needed to operate and maintain your underwater video housing.

Easy View External Mounted Monitor Assembly Instruction Manual & Maintenance Guide

The Easy View External Mounted Monitor Assembly includes the following items:

Housing with Monitor Assembly
AV cable/jack to connect camcorder to Monitor

Note: *The Monitor uses 8 AA size dry batteries with an expected battery life of 3 hours.
To conserve battery power, turn off the monitor when not in use*

Set Up Procedures for Using Easy View Monitor

- Mount Easy View Monitor Assembly to the dove tail on the top of the Underwater Housing. Secure by tightening down thumbscrew just enough to keep the monitor from moving.
- Connect video cable from the Easy View monitor assembly into the waterproof connector on the top of the housing. **Note:** First remove the plug from the connector, line up the index of the connector and tighten it down finger tight.
- To power up the EasyView monitor, rotate the on/off control knob on the left side. The green dot indicates ON; the red dot indicates OFF.
- To change batteries: Remove the rear cover by loosening both thumb screws. Lift off the cover to expose the battery compartment. Remove the battery pack and replace the batteries.
- At the end of the dive be sure to turn off the power to the monitor. Unplug the video cable and replace the plug on the housing. Remove the EasyView Monitor from the housing and thoroughly rinse it in clean water.
- If the Monitor will be idle for an extended period of time the batteries should be removed from the battery pack.

